

**50 YEARS OF INNOVATION**  
**ZERO COST INVESTMENT**  
**HIGH DEMAND PRODUCT**



## TITAN BRUTE 3

Tough, durable design. The name means what it says: Built tough for keeping the job moving in the roughest conditions, it's a BRUTE. The all-steel, solid-welded and double wall design of the Titan Brute Shields was made for heavy-duty trench safety work. These shields rely on thick, reinforced formed steel for unwavering toughness in the trench. They were engineered for durability and deep depths.

Each shield is crafted with high taper reinforced knife edges, which increase the pipe area by allowing a tighter trench. Uninterrupted reinforced vertical steel end tubes mean "no bend back ends." It's also easy to handle with its perfectly positioned lift points. Spreaders are located on the very outside edge for maximum inside clearance.



**TITAN BRUTE 3**  
Brute Series



### FEATURES

- Formed Steel Design
- Continuous Steel Members
- 18" High Tapered Knife Edge
- Internal Pounding Members
- Reinforced Knife Edge
- Internal Stacking System
- Easy Slide Outside Edge
- One C Soil Depth Rating
- Vertical Reinforced Pounding Area
- Reinforced Through Wall Sockets
- 7" Solid Steel Sockets
- 1" Thick Pounding Pads
- 2-½" Solid Stacking Lug Bar
- ½" x 3" Cutting Bar



### SPECIFICATIONS

**Primary Uses:** Spot Repairs and Mainline Work  
**Excavator Weight Range:** 32K to 98K  
**Production Depth:** 16' to 28'  
**Side Wall:** -5"



LENGTH	4'	SHIELD WT	MACH WT	5'	SHIELD WT	MACH WT
	16' - ST	4525	30K	16' - K	4786	32K
	18' - ST	4784	32K	18' - K	5210	35K
	20' - ST	5259	35K	20' - K	5665	38K
	22' - ST	5686	38K	22' - K	6103	41K
	24' - ST	6142	41K	24' - K	6537	44K
	26' - ST	6531	44K	26' - K	6926	46K

LENGTH	6'	SHIELD WT	MACH WT	8'	SHIELD WT	MACH WT
	16' - K	5638	38K	16' - K	7132	48K
	18' - K	6162	41K	18' - K	7815	52K
	20' - K	6718	45K	20' - K	8530	57K
	22' - K	7313	49K	22' - K	9161	61K
	24' - K	7753	52K	24' - K	9855	66K
	26' - K	8212	55K	26' - K	10,436	70K

LENGTH	10'	SHIELD WT	MACH WT
	16' - K	8715	58K
	18' - K	9541	64K
	20' - K	10,353	69K
	22' - K	11,143	74K
	24' - K	11,981	80K
	26' - K	12,675	85K

