

**50 YEARS OF INNOVATION**  
**ZERO COST INVESTMENT**  
**HIGH DEMAND PRODUCT**



## TITAN BRUTE 9

Tough, durable design. The name means what it says: Built tough for keeping the job moving in the roughest conditions, it's a BRUTE. The all-steel, solid-welded and double wall design of the Titan Brute Shields was made for heavy-duty trench safety work. These shields rely on thick, reinforced formed steel for unwavering toughness in the trench. They were engineered for durability and deep depths.

Each shield is crafted with high taper reinforced knife edges, which increase the pipe area by allowing a tighter trench. Uninterrupted reinforced vertical steel end tubes mean "no bend back ends." It's also easy to handle with its perfectly positioned lift points. Spreaders are located on the very outside edge for maximum inside clearance.



**TITAN BRUTE 9**  
Brute Series



### FEATURES

- 18" Knife Edge Taper
- 6" (2x) Strong Pipe Sockets
- 1½" Thick Pounding Pads
- 3" Solid Stacking Lug Bar
- ½" x 3" Cutting Bar



### SPECIFICATIONS

**Production Depth:** 20' to 50'  
**Side Wall:** -9½"



LENGTH	4'	SHIELD WT	MACH WT	5'	SHIELD WT	MACH WT
	16' - ST	8249	55K	16' - K	9996	56K
	18' - ST	8929	60K	18' - K	10,772	60K
	20' - ST	9583	64K	20' - K	11,520	64K
	22' - ST	10,275	69K	22' - K	12,299	68K
	24' - ST	10,967	73K	24' - K	13,078	73K
	26' - ST	11,659	78K	26' - K	13,857	77K

LENGTH	6'	SHIELD WT	MACH WT	8'	SHIELD WT	MACH WT
	16' - K	9996	67K	16' - K	12,670	84K
	18' - K	10,772	72K	18' - K	13,630	91K
	20' - K	11,520	77K	20' - K	14,589	97K
	22' - K	12,299	82K	22' - K	15,564	104K
	24' - K	13,078	87K	24' - K	16,539	110K
	26' - K	13,857	92K	26' - K	17,514	117K

LENGTH	10'	SHIELD WT	MACH WT
	16' - K	15,092	101K
	18' - K	16,198	108K
	20' - K	17,353	116K
	22' - K	18,486	123K
	24' - K	19,619	131K
	26' - K	20,752	117K

