
50 YEARS OF INNOVATION ZERO COST INVESTMENT HIGHDEMAND PRODUCT



TITAN BASIC 6

The Titan Basic Series 6 is an all steel trench shield that is designed for occasional mainline work.

The 17' C-Soil Depth rating combined with a sloping program will cover a maximum range of job situations. The weight and durability, as well as its affordability, make it a perfect match for excavators in the 19 to 24 metric ton class. More room allows for faster mainline production for jobs laying up to 18' lengths of pipe. An alternative depth rating is available. (25' C-Soil)



TITAN BASIC 6 Titan Basic Series



FEATURES

- Tamping Blocks
- Lifting Lugs
- Forged Spreader Pins
- High Taper
- 3/8" x 3" Cutting Bar
- Solid Welded



ACCESSORIES

- Stacking Lugs & Plates
- Tandum Lugs & Plates
- Chain Slings
- Drop Ons



SPECIFICATIONS

Primary Uses: Occasional Mainline Work Excavator Weight Range: 38K to 48K **Production Depth:** 15' to 17' Side Wall: - 6"

BENCHMARK





MODEL	WEIGHTS	SPREADER TABLE	STANDARD Depth Ratings			
Model - H x L style	Weight		A Soil	B Soil	C Soil	
B# - #x#-#	POUNDS			FEET		
B6 - 5' x 20' - K	4787	E	32'	19'	15'	
B6 - 7.5' x 20' - K	6900	E	38'	22'	17'	
B6 - 5' x 24' - K	5643	E	27'	16'	12'	
B6 - 7.5' x 24' - K	7990	E	32'	19'	15'	
BASIC 6: Extra Depth Available (25' C-Soil)						

STYLE: K - Knife ST - Stacker Knife

E SPREADERS				
Lenght	Weight			
18 in	307 lb			
24 in	394 lb			
30 in	480 lb			
36 in	567 lb			
42 in	654 lb			
48 in	741 lb			
54 in	827 lb			
60 in	914 lb			
72 in	1088 lb			
84 in	1261 lb			
96 in	1435 lb			
ADJ.	450 lb			
8" SPR SET OF 4				

\bigcirc	VERTICAL CLEARANCES					
	Height (ft)	5'	7.5'			
	Rear Pipe (in)	27	47'			
\	Height (ft)	27	26			



^{*} Clearances with the increased depth rating.