

TITAN BASIC 5

Steel Trench Box

Utility Trench Boxes | Titan Series

The Basic 5 (B5) model is a series of shields for the small excavators. Built to work well in 12' length sewer line installations. The weight, durability and depth ratings for this model are ideal for any contractor. if you have a machine in the 6 metric ton to 19 metric ton class, this is a great shield for them to consider. This will definitely provide the protection needed while increasing main line sewer production.

ACCESSORIES

- Drop Ons
- Chain Slings
- Tandum Lugs & Plates
- Stacking Lugs & Plates (all accessories sold separately)

FEATURES

- · High Taper
- Lifting Lugs
- Solid Welded
- Tamping Blocks
- 3/8"x 3" Cutting Bar
- Forged Spreader Pins

Model				Weight LB	"C" Spreaders Table		th Rat	ing		
Mode	el <u>-</u> l	Н	x L	-	Style			A Soil	B Soil	C Soil
B5	- [5'	x 12'	-	K	2195	С	38'	22'	17'
B5	- [5'	x 14'		K	2472	С	38'	22'	17'
B5	- [5'	x 16'	-	K	2793	С	31'	18'	14'
B5	- 7	.5'	x 12'	-	K	3095	С	38'	22'	17'
B5	- 7	.5'	x 14'	-	K	3450	С	38'	22'	17'
B5	- 7	.5'	x 16'	-	K	4295	С	38'	22'	17'

0						
Horizontal Clearances						
Lengt <mark>h, FT</mark>	12'	14'	16'			
Front to Rear, IN	124"	148"	160"			

"C" Spreaders Table				
Length, IN	Weight, LB			
18"	210			
24"	267			
30"	324			
36"	381			
42"	438			
48"	496			
54"	553			
60"	610			
72"	724			
84"	838			
96"	953			
ADJ	290			
6" SPR SET OF 4				

3/4" Pounding Pads, (IN)	14"	14"	26"

	Vertical Clearances				
	(14') (16			(16')	
$ \bigvee$	Height, FT	4'	7.5'	7.5'	
	Rear Pipe, IN	32"	46"	46"	
	Front Pipe, IN	32"	46"	32"	

Specifications				
Primary Uses	Occasional Mainline Wor			
Excavator Weight Range	12K to 38K			
Production Depth	14' to 17'			
Side Wall	- 5"			



800.580.4195

cs@bmssi.ca

shoringrental.com