

TITAN BASIC 6

Steel Trench Box

Utility Trench Boxes | Titan Series

Both the Basic 6&8's are a perfect match for many of today's contractors. The 17' C-Soil Depth rating combined with sloping program will cover a maximum range of job situations. The weight and durability as well as its affordability make it a perfect match for excavators in the 19 metric ton to 24 metric ton class. More room allows for faster mainline production for jobs laying up to 18' lengths of pipe. An alternative depth rating is available. (25' C-Soil.)

ACCESSORIES

- Drop Ons
- Chain Slings
- Tandem Lugs & Plates
- Stacking Plates & Lugs (all accessories sold separately)

FEATURES

- High Taper
- Lifting Lugs
- Forged Pins
- Solid Welded
- Tamping Blocks
- 3/8"x 3" Cutting Bar



Model	Weight LB	"E" Spreaders Table	Depth Rating FT		
			A Soil	B Soil	C Soil
Model - H x L - Style					
B6 - 5' x 20' - K	4787	E	32'	19'	15'
B6 - 7.5' x 20' - K	6900	E	38'	22'	17'
B8 - 5' x 24' - K	5643	E	27'	16'	12'
B8 - 7.5' x 24' - K	7990	E	32'	19'	15'
BASIC 6&8: Extra Depth Available (25' C-Soil)					

"E" Spreaders Table	
Length, IN	Weight, LB
18"	307
24"	394
30"	480
36"	567
42"	654
48"	741
54"	827
60"	914
72"	1088
84"	1261
96"	1435
ADJ	450
8" SPR SET OF 4	

Horizontal Clearances				
Length, FT	20'	*20'	24'	*24'
Front to Rear, IN	214"	182"	266"	206"

*Clearances with the increased depth rating

3/4" Pounding Pads, (IN)	50"	50"	74"	74"
--------------------------	-----	-----	-----	-----

Vertical Clearances			
Height, FT	5'	7.5'	
Rear Pipe, IN	27"	47"	
Front Pipe, IN	27"	26"	

Specifications	
Primary Uses	Occasional Mainline Work
Excavator Weight Range	38K to 48K
Production Depth	15' to 17'
Side Wall	- 6"