

Category	Trenshore		
Primary Uses	Light Shoring Work		
Excavator Weight Range	Hand		
Production Depth	5' to 12'		
Panel Thickness	- 2-1/2"		
Panel Heights	2', 3.5', 5', 7', 9' and 12'		
Panel Lengths	6'. 8'. 10' and 12'		

TRENSHORE

Aluminum Trench Box

Your Safety is Our Priority Trenshore is a lightweight, versatile shoring system designed to offer simple, cost effective shoring. We have available stock ready to ship. Certified hydraulic TrenShore kits have the option to come with our patent pending TrenchLock safety system. Included in each kit are a hydraulic pump and hoses. TrenShorehas many great features that traditional shoring systems don't have. These features increase safety, productivity and versatility inside the trench. Robust Components: Oversized piston rods with triple seal technology greatly reduce costly leaks and downtime. An inner tube is drawn over the mandrel for a tight fit. Easy to lift and move around on the job site: This incredibly lightweight and versatile system can be moved around the job using your bare hands. Safety Finger Guard: Oversized safety finger guards help avoid potential pinch points while keeping connections clean. Big-Block Standoff: Traditional shoring systems have high tolerance spreader-to-side rail connections. We call this a small block standoff. When dirt falls into this connection, it creates more resistance and becomes harder to use. Our big block standoff design allows dirt to fall through the connection and to keep everything running smoothly.

Features & Benefits

- Pin-On Extensions
- Rotating Finger Guard
- Modular Panel Design
- Over-Sleeve Protection
- Hosed Rating 5,000 PSI
- Fittings Rated 2,500 PSI
- · Certified Repair Program
- Zinc Coated Clevis Pins for easy assembly
- Tested double the capacity before shipment
- Heavy duty high strength aluminum vertical rails
- · Quickly assembles or
- Positive Triple Seal Cylinders disassembles for use or storing

System	Model	Wgt	Depth	1	Space
2'	1727	24	15'	/	4′
	2236	28	15'	1	4'
	2542	30	15'	/	4′
	3456	33	15'	/	4'
	4064	35	15'	/	4′
	5288	38	15'	/	4'
3.5′	1727	47	15'	/	4′
	2236	49	15'	/	4′
	2542	52	15'	/	4′
	3456	59	15'	/	4′
	4064	64	15′	/	4′
	5288	72	15'	1	4′

System	Model	Wgt	Depth / Space
5′	1727	60	15' / 4'
	2236	62	15' / 4'
	2542	68	15' / 4'
	3456	72	15' / 4'
	4064	75	15' / 4'
	5288	78	15' / 4'
7'	1727	75	15' / 4'
	2236	78	15' / 4'
	2542	83	15' / 4'
	3456	93	15' / 4'
	4064	100	15' / 4'
	5288	111	15' / 4'

System	Model	Wgt	Depth	1	Space
9'	1727	96	15'	1	4'
	2236	108	15'	1	4'
	2542	110	15'	1	4′
	3456	114	15′	1	4'
	4064	116	15'	1	4'
	5288	131	15′	/	4'
12'	1727	107	15'	/	4'
	2236	114	15'	/	4'
	2542	118	15'	1	4'
	3456	122	15′	1	4'
	4064	124	15′	1	4'
	5288	130	15′	1	4'

Trenshore Systems

A variety of systems are available from 2' to 12'. Both rails and cylinders come shipped in cardboard boxes partially assembled, making shipping faster and safer at a reduced rate



800.580.4195

cs@bmssi.ca

shoringrental.com